LONG HAUL STEER



CSL 16

APPLICATIONS:

18-Wheeler

TIRE FEATURES:

- 5-rib tread design with special tread compounds enhances even wear and traction in line-haul steer axle positions.
- Multiple sipes and shoulder decoupling grooves enhance tire wear and traction.
- Bead and belt designed package for increased tire performance and multiple retreads.
- SmartWay verified, low rolling resistance tire.



Size	Load Index Speed Symbols	PR	Load Range	Standard Rim	Max Load Single Dual (lbs)	Max Air Single Dual (psi)	Overall Diameter (in)	Section Width (in)	Revolutions per mile	Tread Depth (32nds)	SmartWay
295/75R22.5	144/141M	14	G	9	6175 5675	110 110	39.92	11.73	520	18	Υ
11R22.5	144/142M	14	G	8.25	6175 5840	105 105	41.5	10.98	501	18	Υ
11R22.5	146/143M	16	Н	8.25	6610 6005	120 120	41.5	10.98	501	18	Υ
285/75R24.5	144/141M	14	G	8.25	6175 5675	110 110	41.34	11.14	503	18	Υ
11R24.5	146/143M	14	G	8.25	6610 6005	105 105	43.46	10.98	478	18	Υ
11R24.5	149/146M	16	Н	8.25	7160 6610	120 120	43.46	10.98	478	18	Υ

Interested in this product? Let us help get you in touch with a sales representative who can guide you through the purchasing process and provide you with excellent customer service!